

# SOURCE LED

## Business FIRST – GU5,3

- EXCELLENT QUALITY OF LIGHT
- UP TO 85% OF ENERGY SAVINGS - DURABILITY AND LIFESPAN OF 30 000H
- INTERCHANGEABLE WITH THE TRADITIONAL MR16
- ECOLOGICAL (NO MERCURY) - NO UV EMISSION

### THOM63488 – THOM63518





5xCHIPSET SMD AOT



	6W (éq. 50W)
	3000°K – 4000°K
	400lm – 420lm
	80
	38°
	30 000 H

FEATURES	THOM63488	THOM63518
CODE EAN	3760230663488	3760230663518
BASE	GU5,3	
POWER CONSUMPTION	6W (EQ. HALOGEN 50W)	
LUMINOUS FLUX	400lm(±8%)	420lm(±8%)
CCT	3000°K	4000°K
BEAM ANGLE	38°	
LUMINOUS EFFECIENCY	67lm/W	69lm/W
POWER FACTOR	>0,6 (depending on driver)	
CRI	> 80	
PROTECTION INDEX	IP20	
INPUT VOLTAGE	12V AC	
DIMENSIONS (DxH)	Ø50x50mm	
OPERATING TEMPERATURE	-20°C ~+45°C	
STORAGE TEMPERATURE	-40°C ~+85°C	
WEIGHT	45g	
LIFESPAN	~ 30 000H	



PACKAGING	Qty	Dimensions (LxIxH)	Net Weight	Gross Weight
UNITARY	1	55x55x55mm	0,05kg	0,07kg
INNER BOX	10	290x95x170mm	0,5kg	0,7kg
MASTER BOX	100	505x305x365	5kg	7kg

